



atreaLED

Fixed LED downlight with flood reflector.

Lightfixture body made of aluminium. Passive cooling of the LED chip for optimum service life and reliability.

Deep reflector that creates a well balanced light pattern with good efficiency and high anti-glare.

Available in a variation of LED spectrum colours.

Including electronic gear with 3,0 meter cable and 2-pin plug.

Material
Colour temp [K]
Design LED life
CRI
Initial MacAdam
Power
Nominal Voltage
Form protection
Weight

Die-cast aluminium
 2700 K / 3000 K / 4000 K
 L70 B10 > 50 000 h (T_a 25°)
 90
 3 SDCM
 31 W
 230/240 V, 50 Hz
 IP 20. Class III. CE-approved
 1,4 kg

Dimensions [mm] / Saw instructions

∅ 170 mm



Colours [*]

1

2

3



Item No.	Description	Painting colour	Power	Lumen output	EEC	LED Colour temperature	Amount/Fuse 16 A C-type	Amount/Fuse 16 A B-type
161027-927-00[*]	atreaLED, Flood 60°, 927	[*]	31 W	2900 lm	A+	2700 K	51	32
161027-930-00[*]	atreaLED, Flood 60°, 930 BBL	[*]	31 W	2900 lm	A+	3000 K B BBL	51	32
161027-935-00[*]	atreaLED, Flood 60°, 935	[*]	31 W	2900 lm	A+	3500 K	51	32
161027-940-00[*]	atreaLED, Flood 60°, 940	[*]	31 W	2900 lm	A+	4000 K	51	32

Caleidoscope