



modus 60120

Energy efficient LED general light fixture for mounting in T24 ceiling profile with module 600x1200 mm.

Equipped with 2 parallel double-parabolic reflectors in MIRO® Silver material with selectable optics for ceiling heights between 2.5 to 4 meters (narrow or flood reflector).


Optional RAL color on request.

By selecting the corresponding drive unit, luminaires can be obtained in different lumen-out packages / wattage.

Material
Colour temp [K]
Design LED life
CRI
Initial MacAdam
Nominal Voltage
Form protection
Weight
Dial

Powder coated steel sheet
 3000 / 3500 K or 4000 K
 L80 B10 > 50 000 h (T_a 25°)
 +80
 3 SDCM
 230/240 V, 50 Hz
 IP 20. Class II. CE-approved
 1,2 kg
 On request

Dimensions [mm]



Colours [*]



Item No.	Description	Reflector /Beam	Painting colour	Energy consumption	Lumen output	EEC	Colour temperatur, CRI	Amount / 16 A C-type	Amount / 10 A C-type
170130 830 60120 0[*]	modus 60120, 830, 2500-5832 lm	Flood	[*]	20 - 50 W	2500 - 5832 lm	A++	3000 K, CRI > 80	Select driver	Select driver
170130 830 60120 2[*]	modus 60120, 830, 2500-5832 lm	Narrow	[*]	20 - 50 W	2500 - 5832 lm	A++	3000 K, CRI > 80		
170130 835 60120 0[*]	modus 60120, 835, 2500-5832 lm	Flood	[*]	20 - 50 W	2500 - 5832 lm	A++	3500 K, CRI > 80		
170130 835 60120 2[*]	modus 60120, 835, 2500-5832 lm	Narrow	[*]	20 - 50 W	2500 - 5832 lm	A++	3500 K, CRI > 80		
170130 840 60120 0[*]	modus 60120, 840, 2500-5832 lm	Flood	[*]	20 - 50 W	2500 - 5832 lm	A++	4000 K, CRI > 80		
170130 840 60120 2[*]	modus 60120, 840, 2500-5832 lm	Narrow	[*]	20 - 50 W	2500 - 5832 lm	A++	4000 K, CRI > 80		
161005 500	Driver unit 500 mA with quick connection for luminaire and 3.0 meter cord with plug.			20 W	2500 lm (3000 K)			68	41
161005 700	Driver unit 700 mA with quick connection for luminaire and 3.0 meter cord with plug.			30 W	3322 lm (3000 K)			51	31
161005 1050	Driver unit 1050 mA with quick connection for luminaire and 3.0 meter cord with plug.			40 W	4827 lm (3000 K)			42	26
161005 1300	Driver unit 1300 mA with quick connection for luminaire and 3.0 meter cord with plug.			50 W	5832 lm (3000 K)			30	18

Caleidoscope