



ultraBEAM Multi G2

A multifunctional energyefficient LED general lighting luminaire for installation on cable trays or wire.

Double parabolic optics for ceiling heights from 3 to 7 meters. Available with narrow or medium beam reflector.

Fixture equipped with 5 × 2.5 mm² through wiring.


Easy installation with cables going through the luminaire, thanks to the fold-down panels on each side that allows installation of cable on already mounted luminaire.

7-years LED warranty.

Material
Colour temp [K]
Design LED life
CRI
Initial MacAdam
Lumen range
Nominal Voltage
Form protection
Weight
Dial

Galvanized steel
 3000 / 3500 K or 4000 K
 L80 B10 > 50 000 h (T₀ 25°)
 +80
 3 SDCM
 6000 - 7500 lumen
 230/240 V, 50 Hz
 IP 20. Class I. CE-approved
 On request

Dimensions [mm]



Easy installation





Item: 180828-001

Accessory: Suspension bracket F. wire
 Require 2 pcs / luminaire

Easy electrical wiring

5 - pole terminal in each luminaire end



Item No.	Description	Reflector /Beam	Painting colour	Energy consumption	Lumen output	EEC	Colour temperature, CRI	Amount/Fuse 16 A C-type	Amount/Fuse 10 A C-type
150130 830 13 14 G2	ultraBEAM LED Multi G2 8000 lm, 830	Flood	Galvanized	69 W	7 360 lm	A++	3000 K, CRI > 80	40	24
150130 830 23 14 G2	ultraBEAM LED Multi G2 8000 lm, 830	Narrow	Galvanized	69 W	7 455 lm	A++	3000 K, CRI > 80	40	24
150130 835 13 14 G2	ultraBEAM LED Multi G2 8000 lm, 835	Flood	Galvanized	68 W	7 511 lm	A++	3500 K, CRI > 80	40	24
150130 835 23 14 G2	ultraBEAM LED Multi G2 8000 lm, 835	Narrow	Galvanized	68 W	7 512 lm	A++	3500 K, CRI > 80	40	24
150130 840 13 14 G2	ultraBEAM LED Multi G2 8000 lm, 840	Flood	Galvanized	68 W	7 567 lm	A++	4000 K, CRI > 80	40	24
150130 840 23 14 G2	ultraBEAM LED Multi G2 8000 lm, 840	Narrow	Galvanized	68 W	7 580 lm	A++	4000 K, CRI > 80	40	24
150130 830 12 14 G2	ultraBEAM LED Multi G2 7000 lm, 830	Flood	Galvanized	59 W	6 055 lm	A++	3000 K, CRI > 80	40	24
150130 830 22 14 G2	ultraBEAM LED Multi G2 7000 lm, 830	Narrow	Galvanized	59 W	6 375 lm	A++	3000 K, CRI > 80	40	24
150130 835 12 14 G2	ultraBEAM LED Multi G2 7000 lm, 835	Flood	Galvanized	59 W	6 055 lm	A++	3500 K, CRI > 80	40	24
150130 835 22 14 G2	ultraBEAM LED Multi G2 7000 lm, 835	Narrow	Galvanized	59 W	6 375 lm	A++	3500 K, CRI > 80	40	24
150130 840 12 14 G2	ultraBEAM LED Multi G2 7000 lm, 840	Flood	Galvanized	59 W	6 055 lm	A++	4000 K, CRI > 80	40	24
150130 840 22 14 G2	ultraBEAM LED Multi G2 7000 lm, 840	Narrow	Galvanized	59 W	6 375 lm	A++	4000 K, CRI > 80	40	24
181828-001	Suspension bracket F. wire	N/A	Galvanized	N/A	N/A	N/A	N/A	N/A	N/A

Caleidoscope