

## ecoBEAM LED Opal track

Versatile and energyefficient LED luminaire for use as general lighting with 3-phase track system. Easy hung directly ontop of track profile.

Opal LED diffusors creating a wellbalanced and soft light picture.


Including LED track driver integrated inside 3-phase track profile.

Material Colour temp [K] Design LED life CRI Initial MacAdam Lumen Nominal Voltage Form protection Dali

Dimensions [mm]

Powder painted steel 3000 K / 3500 K or 4000 K  $L_{g0} B_{10} > 70 000 \text{ h}(T_{a}25^{\circ})$  +80 3 SDCM 4 910 Im 230/240 V, 50 HzIP 20. Class III. CE-approved. On request





Item No.	Description	Opal diffusor	Painting colour	Energy consumption	Lumen output	EEC	Colour temperature, CRI	Amount/Fuse 16 A C-type	Amount/Fuse 10 A C-type
161005 830 20 1(*) T	ecoBEAM LED Opal Track, 835, FLOOD	Flood	[*]	44 W	4 910 lm	A++	3000 K, CRI > 80	40	24
161005 835 20 1(*) T	ecoBEAM LED Opal Track, 835, FLOOD	Flood	[*]	44 W	4 910 lm	A++	3000 K, CRI > 80	40	24
161005 840 20 1(*) T	ecoBEAM LED Opal Track, 835, FLOOD	Flood	[*]	44 W	4 910 lm	A++	3000 K, CRI > 80	40	24

Caleidoscope