




plainLED G4 DOT™ Mini

LED-spotlight with unique combined driver and adaptor designed for quick and easy installation to Kaleidoscope grid ceiling systems.

The spotlight unit is attached by three strong neodymium magnets with permanent traction to the grid ceiling profile.



Material

Colour temp [K]
Design LED life
CRI
Lumen
Initial MacAdam
Nominal Voltage
Form protection
Weight
Colours

Die-cast aluminium and plastic housing
 3500 K
 L70 B10 > 50 000 h (T₀ 25°)
 > 90
 1020 lm
 2 SDCM
 230/240 V, 50 Hz
 IP 20, Class III, CE-approved
 0,48 kg
 White, grey, black (others on request)
 Steel profile x > 50 mm.
 a = ø 58 mm
 b = 85 mm

Mounting Dimensions



Item No.	Description	Painting colour	Power	Lumen output	EEC	LED Colour	Amount/ Fuse 16 A C-type	Amount/ Fuse 16 A B-type
016-93501-1501-350-DOT-01	plainLED G4 DOT™ Mini, White, Spot 15°, 935	White	14 W	1020 lm	A+	3500 K	69 pcs	41 pcs
016-93501-2601-350-DOT-01	plainLED G4 DOT™ Mini, White, Medium 26°, 935	White	14 W	1020 lm	A+	3500 K	69 pcs	41 pcs
016-93501-4001-350-DOT-01	plainLED G4 DOT™ Mini, White, Flood 40°, 935	White	14 W	1020 lm	A+	3500 K	69 pcs	41 pcs
031-010-01	Power Cable 4,0 m (2x0,72 mm ²) 2 pin EU plug + IEC C7	White						
031-010-01-UK	Power Cable 4,0 m (2x0,72 mm ²) 2 pin UK plug + IEC C7	White						

Caleidoscope