



## atreaLED G4

LED downlight with deep reflector and body made of aluminium. Passive cooling of the LED chip for optimum service life and reliability.


Anodized aluminium reflector that creates a well balanced light pattern with very high efficiency.

Including electronic gear with quick connector and 3,0 meter main power cable with 2-pin european plug.

**Material**  
**Colour temp [K]**  
**Design LED life**  
**CRI**  
**Initial MacAdam**  
**Power**  
**Nominal Voltage**  
**Form protection**  
**Weight**

Die-cast aluminium  
 3000 K B BBL other on request  
 L90 50 000 h (T<sub>a</sub> 25°)  
 90  
 3 SDCM  
 28 W  
 230/240 V, 50 Hz  
 IP 20. Class III. CE-approved  
 0,85 kg

**Dimensions [mm]**



∅ 150 mm



**Colours**      **White**      **Grey**      **Black**



Item No.	Description	Painting colour	Power	Lumen output	EEC	LED Colour temperatur	Amount/Fuse 16 A C-type	Amount/Fuse 16 A B-type
191125-930-6001-G4	atreaLED, Flood 60°, 930 Below BBL, White	White	28 W	2600 lm	A+	3000 K B BBL	51	32
191125-930-6002-G4	atreaLED, Flood 60°, 930 Below BBL, White	Grey	28 W	2600 lm	A+	3000 K B BBL	51	32
191125-930-6003-G4	atreaLED, Flood 60°, 930 Below BBL, White	Black	28 W	2600 lm	A+	3000 K B BBL	51	32

*Caleidoscope*