


ecoLENS "Very High Output" is our top performance linear LED using 195 lm/watt LED's source.

Adapted for installation in grid ceiling with beam dimensions of 80x100 mm c/c 2,0 m.
Other grid size on request.

Available with five different optics. Narrow 30°, Medium 60°, Wide 90°, XL-Wide 110°, double asymmetric and single asymmetric.

7-years LED warranty.



Material
Colour temp [K]
Design LED life (T<sub>a</sub> 25°)
Max lumen out / wath
Driver lifetime
CRI
Initial MacAdam
Lumen range max
Nominal Voltage
Form protection
Weight
Connection

Dali Dimensions [mm] Powder painted steel 3000 / 3500 K or 4000 K L90 50 000 h 175 Im/W 100 000 h +80 (+90 on request) 3 SDCM 10 500 Im 230/240 V, 50 Hz IP 20. Class III. CE-approved 1,9 kg 3,5 m cable with 2-pin plug on seperate driver On request L1900 x H50 x B35 mm

Item No.	Description	Reflector /Beam	Painting colour	Energy consumption	Lumen output	Colour temperature, CRI	Amount/Fuse 16 A C-type	Amount/Fuse 10 A C-type
221005 830 10 1001 H	ecoLENS LED GRID, 830, White, F2x2	Narrow	White	Select driver *	See selected driver	3000 K, CRI > 80		
221005 830 10 1002 H	ecoBEAM LED GRID, 830, White, F2x2	Medium	White	Select driver *	See selected driver	3000 K, CRI > 80		
221005 830 10 1003 H	ecoBEAM LED GRID, 830, White, F2x2	Wide	White	Select driver *	See selected driver	3000 K, CRI > 80		
221005 830 10 1004 H	ecoBEAM LED GRID, 830, White, F2x2	Double Asymmetric	White	Select driver *	See selected driver	3000 K, CRI > 80		
221005 830 10 1005 H	ecoBEAM LED GRID, 830, White, F2x2	Asymmetric	White	Select driver *	See selected driver	3000 K, CRI > 80		
221005 835 10 1001 H	ecoLENS LED GRID, 835, White, F2x2	Narrow	White	Select driver *	See selected driver	3500 K, CRI > 80		
221005 835 10 1002 H	ecoBEAM LED GRID, 835, White, F2x2	Medium	White	Select driver *	See selected driver	3500 K, CRI > 80		
221005 835 10 1003 H	ecoBEAM LED GRID, 835, White, F2x2	Wide	White	Select driver *	See selected driver	3500 K, CRI > 80		
221005 835 10 1004 H	ecoBEAM LED GRID, 835, White, F2x2	Double Asymmetric	White	Select driver *	See selected driver	3500 K, CRI > 80		
221005 835 10 1005 H	ecoBEAM LED GRID, 835, White, F2x2	Asymmetric	White	Select driver *	See selected driver	3500 K, CRI > 80		
221005 835 10 1001 H	ecoLENS LED GRID, 840, White, F2x2	Narrow	White	Select driver *	See selected driver	4000 K, CRI > 80		
221005 835 10 1002 H	ecoBEAM LED GRID, 840, White, F2x2	Medium	White	Select driver *	See selected driver	4000 K, CRI > 80		
221005 835 10 1003 H	ecoBEAM LED GRID, 840, White, F2x2	Wide	White	Select driver *	See selected driver	4000 K, CRI > 80		
221005 835 10 1004 H	ecoBEAM LED GRID, 840, White, F2x2	Double Asymmetric	White	Select driver *	See selected driver	4000 K, CRI > 80		
221005 835 10 1005 H	ecoBEAM LED GRID, 845, White, F2x2	Asymmetric	White	Select driver *	See selected driver	4000 K, CRI > 80		
161005 DW-VHO	csLED Driver 1500 mA, 3,5 m cable and plug			56 W	9 478 lm		26	16
	csLED Driver, D-switch 0,8-1,9 A, 3,5 m cable and plug			25 - 62 W	4 250 - 10 540 lm		26	16

