



ecoLENS™ LINE

ecoLENS LINE is adapted for installation with our LINE system 100-80.

Available with five different optics. Narrow 30°, Medium 60°, Wide 90°, XL-Wide 110°, double asymmetric and single asymmetric.

7-years LED warranty.

Material	Powder painted steel
Colour temp [K]	3000 / 3500 K or 4000 K
Design LED life (T_a 25°)	L90 50 000 h
Max lumen / watt	175 lm/W
Driver lifetime	100 000 h
CRI	+80 (+ 90 on request)
Initial MacAdam	3 SDCM
Lumen range max	7 800 lm @ 47 W
Nominal Voltage	230/240 V, 50 Hz
Form protection	IP 20, Class III, CE-approved
Weight	1,9 kg
Connection	csLED Driver connection
eSAVE	Yes
Dimensions [mm]	L1409 x W50 x H35 mm

Item No.	Description	Reflector /Beam	Painting colour	Energy consumption	Lumen output	Colour temperature, CRI	Amount/Fuse 16 A C-type	Amount/Fuse 10 A C-type
221005 830 10 1001 L	ecoLENS LINE, 830, Narrow 30°, White	Narrow	White	Select driver *	4400 - 7800 lumen	3000 K, CRI > 80		
221005 830 10 1002 L	ecoLENS LINE, 830, Medium 60°, White	Medium	White	Select driver *	4400 - 7800 lumen	3000 K, CRI > 80		
221005 830 10 1003 L	ecoLENS LINE, 830, Wide 90°, White	Wide	White	Select driver *	4400 - 7800 lumen	3000 K, CRI > 80		
221005 830 10 1004 L	ecoLENS LINE, 830, DA, White	Double Asymmetric	White	Select driver *	4400 - 7800 lumen	3000 K, CRI > 80		
221005 830 10 1005 L	ecoLENS LINE, 830, AS, White	Asymmetric	White	Select driver *	4400 - 7800 lumen	3000 K, CRI > 80		
221005 835 10 1001 L	ecoLENS LINE, 835, Narrow 30°, White	Narrow	White	Select driver *	4400 - 7800 lumen	3500 K, CRI > 80		
221005 835 10 1002 L	ecoLENS LINE, 835, Medium 60°, White	Medium	White	Select driver *	4400 - 7800 lumen	3500 K, CRI > 80		
221005 835 10 1003 L	ecoLENS LINE, 835, Wide 90°, White	Wide	White	Select driver *	4400 - 7800 lumen	3500 K, CRI > 80		
221005 835 10 1004 L	ecoLENS LINE, 835, DA, White	Double Asymmetric	White	Select driver *	4400 - 7800 lumen	3500 K, CRI > 80		
221005 835 10 1005 L	ecoLENS LINE, 835, AS, White	Asymmetric	White	Select driver *	4400 - 7800 lumen	3500 K, CRI > 80		
221005 840 10 1001 L	ecoLENS LINE, 840, Narrow 30°, White	Narrow	White	Select driver *	4400 - 7800 lumen	4000 K, CRI > 80		
221005 840 10 1002 L	ecoLENS LINE, 840, Medium 60°, White	Medium	White	Select driver *	4400 - 7800 lumen	4000 K, CRI > 80		
221005 840 10 1003 L	ecoLENS LINE, 840, Wide 90°, White	Wide	White	Select driver *	4400 - 7800 lumen	4000 K, CRI > 80		
221005 840 10 1004 L	ecoLENS LINE, 840, DA, White	Double Asymmetric	White	Select driver *	4400 - 7800 lumen	4000 K, CRI > 80		
221005 840 10 1005 L	ecoLENS LINE, 840, AS, White	Asymmetric	White	Select driver *	4400 - 7800 lumen	4000 K, CRI > 80		
224	csLED DRIVER 2x(550-1000 mA)						15 pcs	9 pcs
224e	eSAVE LED DRIVER 2x(550-1000 mA)						17 pcs	10 pcs

Caleidoscope