



plainLED G5 Track

LED luminaire with global adapter for mounting in 3-phase rail. Luminaire body made of aluminum castings.

Passive cooling of the LED chip for optimal lifetime and reliability.

MIRO Silver reflector technology that creates a well-balanced light image with very high efficiency.

Driver built into the 3-phase adapter.

Color: white, black or grey.



Material

Colour temp [K]
Design LED life
CRI
Lumen
Initial MacAdam
Nominal Voltage
Form protection
Weight
Colours


Die-cast aluminium and plastic housing
 3000 K B BBL, 3500 K B BBL, 4000 K L90 0 000 h (T₀ 25°)
 90
 2950 lm
 2 SDCM
 230/240 V, 50 Hz
 IP 20. Class III. CE-approved
 0,475 kg
 White, grey, black (others on request)

Mounting

Steel profile x > 50 mm.

Dimensions

a = ø 80 mm
 b = 127 mm
 c = 170 mm



Item No.	Description	Painting colour	Power	Lumen output	Reflector	EEC	LED Colour	Amount/ Fuse 16 A C-type	Amount/ Fuse 16 A B-type
016-93001-**0(a)-TG5	plainLED G5 Track, 930 B BBL	a = 1 = white a = 2 = grey a = 3 = black	23 W	2950 lm	* = 10° (Spot) * = 22° (Medium) * = 38° (Flood) * = 53° (X-Flood)	A+	3000 K Below BBL	68 pcs	40 pcs
016-93501-**0(a)-TG5	plainLED G5 Track, 935 B BBL	a = 1 = white a = 2 = grey a = 3 = black	23 W	2950 lm	* = 10° (Spot) * = 22° (Medium) * = 38° (Flood) * = 53° (X-Flood)	A+	3500 K Below BBL	68 pcs	40 pcs
016-94001-**0(a)-TG5	plainLED G5 Track, 940	a = 1 = white a = 2 = grey a = 3 = black	23 W	2950 lm	* = 10° (Spot) * = 22° (Medium) * = 38° (Flood) * = 53° (X-Flood)	A+	4000 K	68 pcs	40 pcs

Caleidoscope