



## plainLED G5 Track

LED-spotlight with global adapter for mounting in 3-phase rail. Spotlight body made of aluminum die-castings.

Passive cooling of the LED chip for optimal lifetime and reliability. 7-years warranty.

MIRO Silver reflector technology that creates a well-balanced light image with very high efficiency.

Driver built into the global 3-phase adapter.

Color: white, black or grey (other on request)

### Material

Colour temp [K]  
Design LED life  
CRI  
UGR  
System lumen  
Initial MacAdam  
Nominal Voltage  
Form protection  
Weight  
Colours

### Warranty

### Accessories


### On request

### Dimensions

Die-cast aluminium  
3000 K, 3500 K, 4000 K  
L90 > 50 000 h (T<sub>0</sub> 25°)  
> 90  
< 5  
2 950 lm - 128 lm / watt  
2 SDCM  
230/240 V, 50/60 Hz  
IP 20. Class III. CE-approved  
0,475 kg  
White, grey, black (others on request)  
7-years

Honeycomb, **016H-TG5**  
Barndoors, **016B-TG5**

Casambi / Dali



Item No.	Description	Painting colour	Power (System)	Lumen output (System)	Reflector	LED Colour	Amount/ Fuse 16 A C-type	Amount/ Fuse 16 A B-type
016-93001-**0(a)-TG5	plainLED G5 Track, 930 B BBL	α = 1 = white α = 2 = grey α = 3 = black	23 W	2950 lm	* = 10° (Spot) * = 22° (Medium) * = 38° (Flood) * = 53° (X-Flood)	3000 K Below BBL	68 pcs	40 pcs
016-93501-**0(a)-TG5	plainLED G5 Track, 935 B BBL	α = 1 = white α = 2 = grey α = 3 = black	23 W	2950 lm	* = 10° (Spot) * = 22° (Medium) * = 38° (Flood) * = 53° (X-Flood)	3500 K Below BBL	68 pcs	40 pcs
016-94001-**0(a)-TG5	plainLED G5 Track, 940	α = 1 = white α = 2 = grey α = 3 = black	23 W	2950 lm	* = 10° (Spot) * = 22° (Medium) * = 38° (Flood) * = 53° (X-Flood)	4000 K	68 pcs	40 pcs

# Caleidoscope