

smartLED™ BOX



smartLED BOX spotlight/downlight for easy and quick fixing to Kaleidoscope openCELL grid structure ceilings.

Lightfixture body made of aluminium. Passive cooling of the LED source for optimum service life and reliability.

MIRO Silver reflector that creates a well balanced light pattern with very high efficiency.

Available in a variation of LED spectrum colours upon request.

3,0 meter lowvoltage cable from downlight to driver included. Extension cables. 7-years warranty.

Material	Die-cast aluminium
Design LED life	L90 50 000 h (T _a 25°)
CRI	90
Lumen	2950 lm
Energy	23 W
Initial MacAdam	2 SDCM
Nominal Voltage	230/240 V, 50/60 Hz
Form protection	IP 20. Class III. CE-approved
Weight	0,42 kg
Colors	White, Grey, Black
Dimensions [mm]	ø 148 x H 140 mm

3-channel power supply

3 pcs of downlights can be connected to one LED-driver. Low voltage extension cable available for maximum range in ceiling installations.



Item No.	Description	Colour & box size	Power	Lumen	Reflector	LED Colour	Amount/ Fuse 16 A C-type	Amount/ Fuse 16 A B-type
222 3aaa 22 0b DBX-zb	smartLED, Medium 22°, 3000 K B BBL W.	b = 1 White b = 2 Grey b = 3 Black z = 250 250x250 mm z = 200 200x200 mm z = 150 150x150 mm z = 150 100x100 mm	23 W	2950 lm	22° (Medium)	aaa = 930 (3000 K B BBL) aaa = 935 (3500 K B BBL) aaa = 940 (4000 K)	45	27
222 3aaa 38 0b -DBX-zb	smartLED, Flood 38°, 3000 K B BBL W.	b = 1 White b = 2 Grey b = 3 Black z = 250 250x250 mm z = 200 200x200 mm z = 150 150x150 mm z = 150 100x100 mm	23 W	2950 lm	38° (Flood)	aaa = 930 (3000 K B BBL) aaa = 935 (3500 K B BBL) aaa = 940 (4000 K)	45	27
222	smartLED Driver 3x600 mA ON/OFF	White					15	9
222e	eSAVE Driver 3x600 mA	White					17	10
031-020-02	2,0 m (2x0,72 mm ²) 2 pin EU plug + IEC C7, WHITE	White						
031-010-C8C7-2M	Power Cable 2,0 m (2x0,72 mm ²) C8 + C7, White	White						
A-3022	2,0 M extension cable for smartLED spotlights. Male/female connectors.	White						

Caleidoscope